
10 9 8 Model No. 型号 E88#B-WF

Old Model No.: M12B1216W

EVETAR®

SPECIFICATION SHEET

	of Edit ICATION SHEET								
	Material No. 物	料号		M12B1216W					
E	Sensor Spec			1/2"					
	传感器规格			6.4x4.8,8					
	Max Image Circ 最大像面	;ie		Ø9					
Ц	EFL 有效焦距			12mm					
	FNo. F值			F1.8					
		D.对角		38.9°±3°					
_	F.O.V. 视场角	H.水平		30.9°±2°					
D		V.垂直		23°±2°					
	Back Focal Ler 后截距	ngth		6.79mm (Include 0.3Filter+0.5C.G)					
	Lens Effective Diameter	Fro		Ø8.4mm					
	通光口径	Bac 后面		Ø5.5mm					
С	Lens construction 镜头组成			5 Elements					
	OP Distortion 光学 畸变			>-5.6%					
	Resolution 分辨	率		MP					
	Relative Illumir 相对照度	nation	1	>40%					
	Iris 光圈			Fixed					
В	Max Chief Ray 最大主光线入射		е	20.0°					
В	M.O.D 最近物距			0.5m					
	Working Distar 工作物距	ıce		∞					
П	Mount 接口			M12x0.5-6g					
	TTL 光学总长			21.01±0.3mm (Include 0.3 Filter+0.5C.G)					
	Dimension (Øx 外形尺寸	L)		Ø14x15.62mm					
Α	Filter Spec 滤光片规格			A03-016					
	10			9	8				





		<u> </u>							NAME /	DATE	厦 i]力鼎	光电股色	分有限公司	
		<u>^2</u>					DRAW		Budd	Co23.6.17	Xiar	Xiamen Leading Optics Co., Ltd.			
		Â					CHECKE	D	melon +	2023 6.17	ww	www.evetar.com			
0	0	<u>Ô</u>	2023.6.17	新规作成	XKW	PRQ	AUDI.	4.	MOICYO	20236.1	UNLI	UNLESS TOLERANCE		⊕ -€	
RI	ĒV.	NO.	DATE	DESCRIPTION	REVISED	APPR.	APPR.	V	Take	202-06-1	7Single Pa	art Size.±0.1	Portfolio Size.±0	.3 3RD Angle Projection	
			7	6		5		4	4	3	7		2	1	