10		9	8 7 6 5 4 3 2 1]
Model	Model No. 型号 E3137B			R
			EVETAF	<
F Old Model No.: M12B2524IRM12				F
-		ON OUFFT		
		ON SHEET		
Material No. 物料号 E Sensor Spec		M12B2524IRM12 1/2" CCD/CMOS	_	F
传感器规格		6.4x4.8,8		C.
Max Image Circle 最大像面		Ø8mm	18.72 6.79(in air)	
EFL 有效焦距		25mm	3.8 7.5	
FNo. F值		F2.4		
	D.对角			06.3
F.O.V. 视场				
Back Foca	V.垂直		age plane	
后截距		10.26mm (in air)	M12x0.5-6g	
 Lens Effec Diameter 	tive Front 前面	Ø10.2mm		// H
通光口径	Back 后面	Ø6.3mm		<pre>/ </pre>
Lens construction 6人组成		5-3		с
Optics Distortion 光学 畸变		<3.3%	33. 22	
Resolution		5M		
Relative Illumination 相对照度		>50%		
		Fixed		
B取八土儿线八別用		14.9°		B
		0.5m	LEA	
Working Distance 工作物距		00		
Mount 接口		M12X0.5-6g	X TA Z	
TTL 光学总-	K	25mm(in air)	A NAME DATE 厦门力鼎光电股份有限公	10
Dimension 外形尺寸	(ØxL)	Ø15x18.72mm	DRAWN 70 M 70/810.9 Xiamen Leading Optics Co., I	_td.
A Filter Spec		1	- A CHECKED John B.(0.09 WWW.evetar.com 00 ▲ 2018.10.09 新規作成 XH XYL AUDI. D	A
滤光片规格		1	00 ① 2018.10.09 新規作成 XH XYL AUDI. D · Ø. · Ø. · Ø. · Ø. UNLESS TOLERANCE ④ E REV. NO. DATE DESCRIPTION REVISED APPR. APPR. FOUND Single Part Size.±0.1 Portfolio Size.±0.3 3RD Angle F	
10		9 [8 7 6 5 4 3 2 1	