



Capacitive Sensor Series 80 - PNP



Housing M 30 x 1.5

- Capacitive sensor for level and position control
- Housing material: Brass
- Sensing distance 1...30 mm adjustable
- With flange connector M 12 x 1



Technical data	Non-flush mountable
Operating distance S_n	15 mm
Operating distance min. / max. adjustable	1...30 mm
Electrical version	4 - pin DC
Output function	Antivalent
Type PNP	KAS-80-A24-A-M30-PEEK/MS-Y5-1-HP
Art.-No.	KA 1439
Operating voltage (U_B)	10...35 V DC
Voltage drop max. (U_d)	≤ 2.0 V
Permitted residual ripple max.	10 %
Operating current (I_e)	2 x 0...250 mA
No-load current (I_o)	Typ. 15 mA
Frequency of operating cycles max.	50 Hz
Permitted ambient temperature	-25...+70 °C
LED-display	Green / yellow
Protective circuit	Built-in
Degree of protection IEC 60529	IP 67*
Norm	EN 60947-5-2
Connection	Flange connector M 12 x 1 (A-coded)
Housing material	Brass
Active surface	PEEK (FDA 21 CFR 177.2415)
Lid	PA / PPO
Media optimized	Yes
Accessories (delivered with the sensor)	2 nuts M 30 x 1.5
For matching connectors please see our selection of accessories.	

All specifications are subject to change without notice. (07.11.2019)



* With sealed potentiometer screw

Made in Germany