

Part number

MFVN 10.32



Hood, LS-TYPE series, with 4 pegs, M32 top cable entry without adapter, size "57.27", high construction

Product description

Product type	Hood
Series	LS-TYPE
Closing type	With 4 pegs
Size	Size "57.27"
Cable entry	Top cable entry without adapter M32
Specification	High construction

Technical data

IP degree of protection	IP65
--------------------------------	------

Further technical details

Weight	167,50 g
Operating temperature range (min, max)	-40°C...+125°C

Material properties

Colour	RAL 9005 black
RoHs conformity	Compliant
China RoHs - EFUP	E
REACH SVHC substances	No

Approvals / Standards

Certifications	DNV-GL, BV
UL	ECBT2
cUL	ECBT8

General ordering information

EAN13 code	8015747163583
eCl@ss 8.1	27440202
ETIM 7.0	EC000437

Packaging Information


Packaging length	150,00 mm
Packaging height	160,00 mm
Packaging width	300,00 mm
Packaging weight	3,35 kg
Packaging volume	7,20 dm ³
Packaging description	Carton box
Packaging quantity	20 Pcs
Packaging EAN code	8015747187787
Sub-packaging weight	0,84 kg
Sub-packaging description	Plastic packaging
Sub-packaging quantity	5 Pcs
Sub-packaging EAN barcode	8015747187794

Part number

MFVN 10.32



Catalogue drawings



Catalogue drawings

CH..N - MA, MF..N enclosures		size "57.27"		LS-TYPE version																																				
<p>inserts:</p> <table border="0"> <tr><td>CDD</td><td>..... 42 poles + @</td><td>61 *</td></tr> <tr><td>CQE</td><td>..... 18 poles + @</td><td>81 *</td></tr> <tr><td>CSH</td><td>..... 10 poles + @</td><td>89 *</td></tr> <tr><td>CCE</td><td>..... 10 poles + @</td><td>90 *</td></tr> <tr><td>CNE, CSE, JCNE, JCSE</td><td>10 poles + @ 97 and 107 *</td><td></td></tr> <tr><td>CSS</td><td>..... 10 poles + @</td><td>119 *</td></tr> <tr><td>CTE, CTSE **)</td><td>..... 10 poles + @</td><td>127 *</td></tr> <tr><td>CMSE</td><td>..... 3+2 (aux) poles + @</td><td>135 *</td></tr> <tr><td>CMCE</td><td>..... 3+2 (aux) poles + @</td><td>134 *</td></tr> <tr><td>CX</td><td>..... 8/24 poles + @</td><td>151 *</td></tr> <tr><td>MIXO</td><td>..... 3 modules</td><td>160+195 *</td></tr> </table> <p>insert centre distance: 57 x 27 mm</p> <p>* refer to catalogue page CN.12</p>		CDD 42 poles + @	61 *	CQE 18 poles + @	81 *	CSH 10 poles + @	89 *	CCE 10 poles + @	90 *	CNE, CSE, JCNE, JCSE	10 poles + @ 97 and 107 *		CSS 10 poles + @	119 *	CTE, CTSE **) 10 poles + @	127 *	CMSE 3+2 (aux) poles + @	135 *	CMCE 3+2 (aux) poles + @	134 *	CX 8/24 poles + @	151 *	MIXO 3 modules	160+195 *	<p> housings with double lever</p>		<p> hoods with 4 pegs</p>			
CDD 42 poles + @	61 *																																						
CQE 18 poles + @	81 *																																						
CSH 10 poles + @	89 *																																						
CCE 10 poles + @	90 *																																						
CNE, CSE, JCNE, JCSE	10 poles + @ 97 and 107 *																																							
CSS 10 poles + @	119 *																																						
CTE, CTSE **) 10 poles + @	127 *																																						
CMSE 3+2 (aux) poles + @	135 *																																						
CMCE 3+2 (aux) poles + @	134 *																																						
CX 8/24 poles + @	151 *																																						
MIXO 3 modules	160+195 *																																						
<table border="1"> <thead> <tr> <th>description</th> <th>part no.</th> <th>entry M</th> <th>part no.</th> <th>entry M</th> </tr> </thead> <tbody> <tr> <td>bulkhead mounting housing, with 2 levers</td> <td>CHIN 10</td> <td></td> <td></td> <td></td> </tr> <tr> <td>surface mounting housing, high construction, with 2 levers</td> <td>MAPN 10.32</td> <td>32</td> <td></td> <td></td> </tr> <tr> <td>with pegs, side entry, high construction</td> <td></td> <td></td> <td>MHON 10.25</td> <td>25</td> </tr> <tr> <td>with pegs, side entry, high construction</td> <td></td> <td></td> <td>MFON 10.32</td> <td>32</td> </tr> <tr> <td>with pegs, top entry, high construction</td> <td></td> <td></td> <td>MHVN 10.25</td> <td>25</td> </tr> <tr> <td>with pegs, top entry, high construction</td> <td></td> <td></td> <td>MFVN 10.32</td> <td>32</td> </tr> </tbody> </table>		description	part no.	entry M	part no.	entry M	bulkhead mounting housing, with 2 levers	CHIN 10				surface mounting housing, high construction, with 2 levers	MAPN 10.32	32			with pegs, side entry, high construction			MHON 10.25	25	with pegs, side entry, high construction			MFON 10.32	32	with pegs, top entry, high construction			MHVN 10.25	25	with pegs, top entry, high construction			MFVN 10.32	32	<p>**) only in the CHIN 10 enclosure</p> <p>panel cut-out for bulkhead mounting housing in mm</p> <p>- kiln powder coating with RAL 9005 black epoxy polyester powder - RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)</p> <p>dimensions shown are not binding and may be changed without notice</p>		<p>dimensions in mm</p> <p>CHIN 10</p> <p>MAPN 10.32</p> <p>MFON 10.32</p> <p>MFVN 10.32</p> <p>MHON 10.25</p> <p>MHVN 10.25</p>	
description	part no.	entry M	part no.	entry M																																				
bulkhead mounting housing, with 2 levers	CHIN 10																																							
surface mounting housing, high construction, with 2 levers	MAPN 10.32	32																																						
with pegs, side entry, high construction			MHON 10.25	25																																				
with pegs, side entry, high construction			MFON 10.32	32																																				
with pegs, top entry, high construction			MHVN 10.25	25																																				
with pegs, top entry, high construction			MFVN 10.32	32																																				