


- According to DIN EN 61810-1, DIN EN 61810-3 (Type A)
- With forcibly guided contacts
- **Double and reinforced insulation between contact sets acc. to EN 50178**
- High dielectric strength
- High mechanical service life
- High switching reliability
- Compact size
- High thermal continuous current
- High voltage range
- Wash proof model as option

### Applications

- Switchgear for safety technology
- Press controls

### Approvals and Markings



### Technical Data

Relais type		OA 5670
<b>1.0 Relais coil</b>		
1.1 Nominal voltage	DC V	6; 12; 20; 24; 48; 60; 110 (others on request)
1.2 Nominal consumption	W	1.0
1.3 Holding power (at 0.5 x UN)	W	0.25
<b>2.0 Contacts</b>		
2.1 Contact arrangement (Type A)		2 NO and 2 NC; 3 NO and 1 NC
2.2 Contact material		AgSnO <sub>2</sub> + 0.2 μm Au; AgNi + 0.2 μm Au, AgNi + 5 μm Au
2.3 Rated insulation voltage	AC V	250
Switching voltage min./max.	V	AC/DC 10 / DC 250, AC 400 (AC/DC 2 V / 60 V) <sup>1)</sup>
2.4 Limiting continuous current I <sub>th</sub>	A	3 x 6 (see operating voltage limit curve)
Switching current min./max.	A	10 mA <sup>3)</sup> / 6 (2 mA / 0.3 A) <sup>1)</sup>
2.5 Switching power min./max.	VA	0.1 / 1500 (10 mVA / 12 VA) <sup>1)</sup>
Switching power min./max.	W	0.1 <sup>3)</sup> / 200 (10 mW / 12 W) <sup>1)</sup> (s. limit curve for arc-free operation)
2.6 Switching capacity to IEC/EN 60947-5-1		
AC 15 <sup>4)</sup>	AC V/A	NO: 250 / 2 NC: 250 / 1
AC 15 <sup>5)</sup>	AC V/A	NO: 250 / 3 NC: 250 / 1
DC 13 <sup>4)</sup>	DC V/A	NO: 24 / 1 NC: 24 / 1
DC 13 <sup>4)</sup> at 0.1 Hz to UL 508	DC V/A	NO: 24 / 4 NC: 24 / 3
		B300 / R300
2.7 Electrical life	Switching cycles	at 1 s On, 1 s Off (see contacts service life)
at AC 230 V, 6 A, cos φ = 1	Switching cycles	> 2,6 x 10 <sup>5</sup> AgNi
at DC 24 V, 6 A ohmsch	Switching cycles	> 4 x 10 <sup>6</sup> AgNi
2.8 Switching frequency max.	Switching cycles/s	10
2.9 Response time / Release time	ms	Typically 11 / Typically 6
2.10 Contact force NO / NC	cN	≥ 10
2.14 Contact gap	mm	> 0.5 <sup>6)</sup>
<b>3.0 Other</b>		
3.1 Mechanical life	Switching cycles	≥ 50 x 10 <sup>6</sup>
3.2 Temperature range	°C	- 40 ... + 75
3.3 Degree of protection, housing		Solder line proof RT II as option wash proof RT III
3.4 Test procedure		A (group mounting)
3.5 Vibration resistance		10 ... < 60 Hz; 0.35 mm Amplitude IEC/EN 60068-2-6 60 ... 200 Hz, ≤ 5g (all contacts) IEC/EN 60068-2-6 40 / 075 / 04; A / B / D IEC/EN 60068-1
3.6 Climate resistance		
3.7 Short circuit strength 1 kA / AC 250 V	AgNi or AgSnO <sub>2</sub>	6 A gG / gL IEC/EN 60947-5-1

<sup>1)</sup> Values for AgNi-Contacts + 5 μm Au

<sup>2)</sup> 10 A total current at t = 20°C and coil voltage U<sub>N</sub>

<sup>3)</sup> Typical values for AgSnO<sub>2</sub> and AgNi

<sup>4)</sup> Values for AgNi-Contacts

<sup>5)</sup> Values for AgSnO<sub>2</sub>-Contacts

<sup>6)</sup> Over entire service life acc. to DIN EN 61810-3


## Technical Data

3.8	Insulation acc. to IEC 60664-1, EN 50178		<b>Double and reinforced insulation</b>
	Rated insulation voltage	AC V	250
	Pollution degree		3
	Overtoltage category		III
	Test voltage		
	Contact-Coil (1 min)	AC kV eff.	≥ 4
	Left contact-right contact (1 min)	AC kV eff.	≥ 4
	Contact-Coil (1 min)	AC kV eff.	≥ 3
	Contact open (1 min)	AC kV eff.	≥ 1.5
	Transient voltage		
	Contact-Coil (1.2 - 50 μs)	kV	≥ 6
	Clearance and creepage distances		
	Contact-Coil	mm	≥ 8
	Left contact-right contact	mm	≥ 5.5
	Contact-Contact	mm	≥ 4.5
3.9	Weight	g	approx. 21
<b>4.0 Packing</b>			
4.1	On cardboard	Piece	42
4.2	In case package	Piece	210
<b>5.0 Solder method</b>			
5.1	Solder method /-temperature /-duration	°C / s	Wave soldering / 260 / 5

## Design Versions

U <sub>N</sub> (DC V)	Voltage range (DC V)	Resistance at 20°C Ω±10%	OA 5670	
			.52 2NO, 2NC	.48 3NO, 1NC
AgNi10 + 0,2 μm Au-contacts				
6	4.2 ... 8.4	36	3201	3211
12	8.4 ... 16.8	150	3202	3212
20	14.0 ... 28.0	400	3203	3213
24	16.8 ... 33.6	580	3204	3214
48	33.6 ... 67.2	2300	3205	3215
60	42.0 ... 84.0	3600	3206	3216
110	77.0 ... 154.0	12100	3207	3217
AgSnO <sub>2</sub> + 0,2 μm Au-contacts				
6	4.2 ... 8.4	36	3221	3231
12	8.4 ... 16.8	150	3222	3232
20	14.0 ... 28.0	400	3223	3233
24	16.8 ... 33.6	580	3224	3234
48	33.6 ... 67.2	2300	3225	3235
60	42.0 ... 84.0	3600	3226	3236
110	77.0 ... 154.0	12100	3227	3237
AgNi10 + 5 μm Au-contacts				
6	4.2 ... 8.4	36	3241	3251
12	8.4 ... 16.8	150	3242	3252
20	14.0 ... 28.0	400	3243	3253
24	16.8 ... 33.6	580	3244	3254
48	33.6 ... 67.2	2300	3245	3255
60	42.0 ... 84.0	3600	3246	3256
110	77.0 ... 154.0	12100	3247	3257

## Ordering example




## Note


For the use and processing of our PCB relays, please refer to the **application and processing instructions** at [www.dold.com](http://www.dold.com)

\*) /61 cURus approval


**Characteristics**




Operating voltage limit curve



Arc limit curve






Reduction factor for reactive loads




Electrical life for contact material AgNi


Drilling plan (solder side)




OA5670.52\_\_L1 2NO/2NC




OA5670.48\_\_L1 3NO/1NC




OA5670.52\_\_L2 2NO/2NC



OA5670.48\_\_L2 3NO/1NC



OA5670.52\_\_L3 2NO/2NC



OA5670.52\_\_L4 2NO/2NC

Connection for basic grid dimensions 2.5 mm as well as 2.54 mm according to IEC/EN 60097 and IEC 60326 average

Relay socket ET 1415.034 for OA 5670

Article number: 0064297

